

## ■ FULL SCALE WATTS TABLE(STANDARD)

C.T ratio	Phase x Wire	1 X 2	1 X 3	3 X 3								3 X 4				
	P.T ratio	110	110	220	380 110	440 110	3300 110	6600 110	22000 110	22900 110	154KV 110	208 ✓	380✓ 190✓	380 ✓	11400✓ ✓	22900✓ 190✓
	CAL. WATT	0.6KW	1.0KW	2.0KW	1.158KW	1.0KW	1.0KW	1.0KW	1.0KW	0.961KW	1.0KW	2.0KW	2.0KW	4.0KW	1.666KW	1.666KW
5/5	0.6	1	2	4	4	30	60	200	200	1400	2	4	4	100	200	
10/5	1.2	2	4	8	8	60	120	400	400	2800	4	8	8	200	400	
15/5	1.8	3	6	12	12	90	180	600	600	4200	6	12	12	300	600	
20/5	2.4	4	8	16	16	120	240	800	800	5600	8	16	16	400	800	
25/5	3.0	5	10	20	20	150	300	1000	1000	7000	10	20	20	500	1000	
30/5	3.6	6	12	24	24	180	360	1200	1200	8400	12	24	24	600	1200	
40/5	4.8	8	16	32	32	240	480	1600	1600	11.2MW	16	32	32	800	1600	
50/5	6.0	10	20	40	40	300	600	2000	2000	14.0	20	40	40	1000	2000	
60/5	7.2	12	24	48	48	360	720	2400	2400	16.8	24	48	48	1200	2400	
75/5	9.0	15	30	60	60	450	900	3000	3000	21.0	30	60	60	1500	3000	
80/5	9.6	16	32	64	64	480	960	3200	3200	22.4	32	64	64	1600	3200	
100/5	12.0	20	40	80	80	600	1200	4000	4000	28.0	40	80	80	2000	4000	
120/5	14.4	24	48	96	96	720	1400	4800	4800	33.6	48	96	96	2400	4800	
150/5	18.0	30	60	120	120	900	1800	6000	6000	42.0	60	120	120	3000	6000	
200/5	24.0	40	80	160	160	1200	2400	8000	8000	56.0	80	160	160	4000	8000	
250/5	30.0	50	100	200	200	1500	3000	10MW	10MW	70.0	100	200	200	5000	10MW	
300/5	36.0	60	120	240	240	1800	3600	12	12	84.0	120	240	240	6000	12	
400/5	48.0	80	160	320	320	2400	4800	16	16	112.0	160	320	320	8000	16	
500/5	60.0	100	200	400	400	3000	6000	20	20	140	200	400	400	10MW	20	
600/5	72.0	120	240	480	480	3600	7200	24	24	168	240	480	480	12	24	
750/5	90.0	150	300	600	600	4500	9000	30	30	210	300	600	600	15	30	
800/5	96.0	160	320	640	640	4800	9600	32	32	224	320	640	640	16	32	
1000/5	120.0	200	400	800	800	6000	12MW	40	40	280	400	800	800	20	40	
1200/5	144.0	240	480	960	960	7200	14.4	48	48	336	480	960	960	24	48	
1500/5	180.0	300	600	1200	1200	9000	18.0	60	60	420	600	1200	1200	30	60	
2000/5	240.0	400	800	1600	1600	12MW	24.0	80	80	560	800	1600	1600	40	80	
2500/5	300.0	500	1000	2000	2000	15	30.0	100	100	700	1000	2000	2000	50	100	

\* T/D W조정값이 위표의 Calibrating Watt와 같으면 T/D에 대한 FULL SCALE값도 위표와 동일함.